5599 Peachtree Road Atlanta, Georgia 30341-2309

800-295-4655

## **Authorization Agreement**

The Radalink Radon Monitor being used to perform the radon survey of the dwelling referenced below has been approved by the U.S. Environmental Protection Agency for conducting radon measurements. The operator will conduct a radon survey for a **minimum** of 48 hours according to protocols designed for use in residences, as described in the EPA document, "Home Buyer's and Seller's Guide to Radon" (EPA 402-K-00-008). These guidelines were developed specifically to deal with the time-sensitive nature of home purchases and sales.

## The following conditions must be maintained in order to achieve a valid test:

- 1. All exterior windows must be kept closed. Exterior doors must be kept closed except for momentary entry and exit.
- 2. The "closed house conditions" described above must have been maintained for 12 hours prior to the beginning of the test and sustained all during the test.
- 3. The radon monitor cannot be moved, covered, or tampered with in any way.
- 4. High volume, whole-house, and window fans shall not be operated. Fireplaces or wood stoves shall not be operated unless they are a primary heat source.
- 5. Minimize use of dryers, range hoods, bathroom fans and other mechanical systems. Drawing air out of the building may adversely affect the results.
- 6. Do not operate ceiling fans, portable dehumidifiers/humidifiers, portable air filters and window air conditioners within 20 feet of device.
- 7. Heating and air conditioning (including permanently installed heat recovery ventilators) should operate normally. Window unit air conditioners shall operate only in the re-circulation mode.
- 8. Permanently installed mitigation systems must operate for at least 24 hours prior to starting and all during the test.

EPA recommends that radon measurements conducted for real estate transactions be performed using tamperdetection techniques. Be alerted that the Radalink Radon Monitor is equipped with the ability to detect and record when the monitor is moved and anytime the power source is changed. Hourly readings will record any unusual swings in the radon concentration, temperature, relative humidity and barometric pressure. At his discretion, the tester may nullify the test result if it appears that, in his professional judgment, the results are unreliable due to the suspicion of tampering. In that event, the seller may incur the cost of a retest.

## **Authorization Signatures**

I, as the undersigned responsible indivagree to inform all the occupants of this deconditions during the radon test period.	vidual, understand all the above conditions a welling of the conditions above, and agree	
Responsible Individual Printed Name	Title (owner, real estate agent, other)	Date
□ Responsible Individual Signature □ Refused to sign □ VACANT - List who contracted the test	Radon Measurement Technician Signature (Witness)	
Address of property being tested under this Authorization Agree	ment	Scheduled start date